

ORLINE WALL MOUNTED

Wattage Options Available:

	12W/M	17W/M	26W/M (Standard)	36W/M	45W/M
3000K	1630 lm/m	2160 lm/m	3018 lm/m	4129 lm/m	5014 lm/m
4000K	1706 lm/m	2261 lm/m	3254 lm/m	4321 lm/m	5247 lm/m

For all bespoke configurations: for example, linear lengths beyond 15M, low UGR, wattage, colour temperature, tuneable white, corner, square, rectangular, cross and circular shapes. Please contact sales@orlight.com

Standard Straight Lengths (Bespoke Configurations TBC upon Request)

OVERALL LENGTH (MM)							
294 (Non-EM)	2184	4084	5984	7884	9774	11674	13574
364 (Non-EM)	2254	4154	6054	7954	9844	11744	13644
434 (Non-EM)	2324	4224	6124	8024	9914	11814	13714
504 (Non-EM)	2394	4294	6194	8094	9984	11884	13784
574 (Non-EM)	2464	4364	6264	8164	10054	11954	13854
644 (Non-EM)	2534	4434	6334	8234	10124	12024	13924
714 (Non-EM)	2614	4504	6404	8304	10204	12094	13994
784 (Non-EM)	2684	4574	6474	8374	10274	12164	14064
854 (Non-EM)	2754	4644	6544	8444	10344	12234	14134
924 (Non-EM)	2824	4714	6614	8514	10414	12304	14204
994	2894	4784	6684	8584	10484	12374	14274
1064	2964	4854	6754	8654	10554	12444	14344
1134	3034	4924	6824	8724	10624	12514	14414
1204	3104	4994	6894	8794	10694	12584	14484
1274	3174	5064	6964	8864	10764	12654	14554
1344	3244	5144	7034	8934	10834	12734	14624
1414	3314	5214	7104	9004	10904	12804	14694
1484	3384	5284	7174	9074	10974	12874	14764
1554	3454	5354	7244	9144	11044	12944	14834
1624	3524	5424	7314	9214	11114	13014	14904
1694	3594	5494	7384	9284	11184	13084	14974
1764	3664	5564	7454	9354	11254	13154	15044
1834	3734	5634	7524	9424	11324	13224	15114
1904	3804	5704	7594	9494	11394	13294	15184
1974	3874	5774	7674	9564	11464	13364	
2044	3944	5844	7744	9634	11534	13434	
2114	4014	5914	7814	9704	11604	13504	