

ORLINE RECESSED

Wattage Options Available:

	12W/M	17W/M	26W/M (Standard)	36W/M	45W/M
3000K	1630 lm/m	2160 lm/m	3018 lm/m	4129 lm/m	5014 lm/m
4000K	1706 lm/m	2261 lm/m	3254 lm/m	4321 lm/m	5247 lm/m

For all bespoke configurations: for example, linear lengths beyond 15M, low UGR, wattage, colour temperature, tuneable white, corner, square, rectangular, cross and circular shapes. Please contact sales@orlight.com

Standard Straight Lengths (Bespoke Configurations TBC upon Request)

OVERALL LENGTH (MM)							
310 (Non-EM)	2200	4100	6000	7900	9790	11690	13590
380 (Non-EM)	2270	4170	6070	7970	9860	11760	13660
450 (Non-EM)	2340	4240	6140	8040	9930	11830	13730
520 (Non-EM)	2410	4310	6210	8110	10000	11900	13800
590 (Non-EM)	2480	4380	6280	8180	10070	11970	13870
660 (Non-EM)	2550	4450	6350	8250	10140	12040	13940
730 (Non-EM)	2630	4520	6420	8320	10220	12110	14010
800 (Non-EM)	2700	4590	6490	8390	10290	12180	14080
870 (Non-EM)	2770	4660	6560	8460	10360	12250	14150
940 (Non-EM)	2840	4730	6630	8530	10430	12320	14220
1010 (Non-EM)	2910	4800	6700	8600	10500	12390	14290
1080 (Non-EM)	2980	4870	6770	8670	10570	12460	14360
1150	3050	4940	6840	8740	10640	12530	14430
1220	3120	5010	6910	8810	10710	12600	14500
1290	3190	5080	6980	8880	10780	12670	14570
1360	3260	5160	7050	8950	10850	12750	14640
1430	3330	5230	7120	9020	10920	12820	14710
1500	3400	5300	7190	9090	10990	12890	14780
1570	3470	5370	7260	9160	11060	12960	14850
1640	3540	5440	7330	9230	11130	13030	14920
1710	3610	5510	7400	9300	11200	13100	14990
1780	3680	5580	7470	9370	11270	13170	15060
1850	3750	5650	7540	9440	11340	13240	15130
1920	3820	5720	7610	9510	11410	13310	15200
1990	3890	5790	7690	9580	11480	13380	
2060	3960	5860	7760	9650	11550	13450	
2130	4030	5930	7830	9720	11610	13520	

CUT LENGTH (MM)							
294 (Non-EM)	2184	4084	5984	7884	9774	11674	13574
364 (Non-EM)	2254	4154	6054	7954	9844	11744	13644
434 (Non-EM)	2324	4224	6124	8024	9914	11814	13714
504 (Non-EM)	2394	4294	6194	8094	9984	11884	13784
574 (Non-EM)	2464	4364	6264	8164	10054	11954	13854
644 (Non-EM)	2534	4434	6334	8234	10124	12024	13924
714 (Non-EM)	2614	4504	6404	8304	10204	12094	13994
784 (Non-EM)	2684	4574	6474	8374	10274	12164	14064
854 (Non-EM)	2754	4644	6544	8444	10344	12234	14134
924 (Non-EM)	2824	4714	6614	8514	10414	12304	14204
994 (Non-EM)	2894	4784	6684	8584	10484	12374	14274
1064 (Non-EM)	2964	4854	6754	8654	10554	12444	14344
1134	3034	4924	6824	8724	10624	12514	14414
1204	3104	4994	6894	8794	10694	12584	14484
1274	3174	5064	6964	8864	10764	12654	14554
1344	3244	5144	7034	8934	10834	12734	14624
1414	3314	5214	7104	9004	10904	12804	14694

Continued on page 2

ORLINE RECESSED



FROM SOURCE TO SITE

CUT LENGTH (MM)							
1484	3384	5284	7174	9074	10974	12874	14764
1554	3454	5354	7244	9144	11044	12944	14834
1624	3524	5424	7314	9214	11114	13014	14904
1694	3594	5494	7384	9284	11184	13084	14974
1764	3664	5564	7454	9354	11254	13154	15044
1834	3734	5634	7524	9424	11324	13224	15114
1904	3804	5704	7594	9494	11394	13294	15184
1974	3874	5774	7674	9564	11464	13364	
2044	3944	5844	7744	9634	11534	13434	
2114	4014	5914	7814	9704	11604	13504	